

TDH 800 Cabinet - Main Unit

Art. Number 692890



TDH 800. Technology, that can do more.

The cabinet is designed as one system of input and output signals, as such up to 24 PAL programmes or 24 QAM channels are possible; it is extremely compact and can therefore be easily installed on a wall or in a 19 "rack. Whether it is related to the installation, maintenance or repair all inputs, outputs and cables can be easily installed and operated from the front of the TDH 800.

The HF output level of the integrated TDH 800 output amplifier can be software-adjusted within the range 85 dB μ V through 93 dB μ V.

Technical Specifications

ORDER INFORMATION	
EAN Number	5702666928906
CHARACTERISTICS	
Max. LNB control mA	4 x 305 mA
Output level max. @ 60 dB IMD - 24 combined	93 dBµV
FREQUENCY RANGE	
Frequency range (RF OUT) MHz	47-862 MHz
RETURN LOSS	
Return loss (RF OUT) dB	> 10 dB
OPERATIONAL	
Temperature - storage °C	-2070 °C
Humidity - storage %	10 to 90 %
CONNECTORS	
External RF OUT	F-connector
PC interface	RJ 45





connecting the future

Technical Specifications		
MECHANICAL		
Packaging Height m	0.390 m	
Packaging Width m	0.550 m	
Packaging Depth m	0.330 m	
Packaging Volume m3	0.071 m3	
Net Weight kg	10.180 kg	
Tara Weight kg	0.000 kg	
Total Weight kg	10.180 kg	

