



LTE700 QR 12 K (Scan=65)

Art. Number 108070



- LTE Protected
- Tool free assembly - Quick lock dipole and reflector
- Strong, rugged construction
- F-Connector dipole housing
- Excellent F/B ratio and performance across the whole UHF band

## Technical Specifications

### ORDER INFORMATION

EAN Number 5702661080708

### CHARACTERISTICS

Antenna use outdoor  
Polarization vertical or horizontal

### FREQUENCY RANGE

Band UHF  
Channels 21...48  
Frequency range | MHz 470-694 MHz  
LTE protection @ 700Mhz

### GAIN

Gain | dBi 12 dBi

### ELECTRICAL

Front to back ratio - horizontal | dB >20...26 dB  
Impedance |  $\Omega$  75  $\Omega$

### CONNECTORS

Connector Type 1 x F connector, 75 Ohm

### MECHANICAL

Elements 12  
Windload @42 m/s | N 58 N



## Technical Specifications

Beamwidth horizontal   °	± 18 °
Bracketry	Mast bracket - rear
Main material	Aluminium
Weight (kg) TB(D)   kg	1.25 kg
Colour	Black
Packaging	Scantainer
Packing QTY	65
Product Length   mm	1010 mm
Product Width   mm	555 mm
Packaging Height   m	0.000 m
Packaging Width   m	0.000 m
Packaging Depth   m	0.000 m
Packaging Volume   m3	0.000 m3
Net Weight   kg	1.290 kg
Tara Weight   kg	0.068 kg
Total Weight   kg	1.358 kg