



# TRIAX

connecting the future

TDS 65LG RAL 7035, bulk pack

Art. Number 120503



**TRIAX TD Dishes** The difference is clear

Manufactured and tested to the highest standards of precision and quality, TRIAX's easy-to-install dishes offer outstanding performance, durability and reliability.

TDS: Steel TDA: Aluminium

- Unrivalled build quality, whether Steel or Aluminium
  - Hot-dip galvanized steel OR long lasting Aluminium - for extra corrosion protection
  - TRIAX's unique cable protection system
  - Every part, every accessory is weatherproofed
  - 2 years corrosion warranty
  - 5 years functionality warranty
- Outstanding performance
  - High gain for an exceptional signal
- Quick and easy installation
  - One-click mounting system
  - Self-locking screw & nuts
- Logistic friendly
  - Single or Bulk packaging, according to customer needs

TRIAX is your reliable partner, with comprehensive service and support.

[Click here](#) to see our guide on how to install TRIAX satellite dishes.

## Technical Specifications

### ORDER INFORMATION

EAN Number

5702661205033



## Technical Specifications

### CHARACTERISTICS

|                     |           |
|---------------------|-----------|
| F/D ratio           | 0,62      |
| G/T LNB 0.7   dB/K  | 16.0 dB/K |
| X-polarisation   dB | ≤ -25 dB  |
| Offset angle   °    | 26 °      |
| Elevation range   ° | 0...90 °  |

### FREQUENCY RANGE

|                       |                  |
|-----------------------|------------------|
| Frequency range   GHz | 10.7...12.75 GHz |
|-----------------------|------------------|

### GAIN

|                       |        |
|-----------------------|--------|
| Gain @ 11.7 GHz   dBi | 36 dBi |
|-----------------------|--------|

### MECHANICAL

|                                   |                            |
|-----------------------------------|----------------------------|
| Height (cm)   cm                  | 66 cm                      |
| Width (cm)   cm                   | 60 cm                      |
| LNB holder                        | 40                         |
| Mast bracket diameter   mm        | 30...60 mm                 |
| Reflector type                    | Offset                     |
| Beamwidth   °                     | 3.1 °                      |
| Main material                     | Galvanized steel (hot-dip) |
| Arm Colour                        | Raw                        |
| Colour                            | RAL 7035 - Light grey      |
| Packing QTY                       | 220                        |
| Packaging Height   m              | 0.010 m                    |
| Packaging Width   m               | 0.600 m                    |
| Packaging Depth   m               | 0.660 m                    |
| Packaging Volume   m <sup>3</sup> | 0.004 m <sup>3</sup>       |
| Net Weight   kg                   | 3.400 kg                   |
| Tara Weight   kg                  | 0.000 kg                   |
| Total Weight   kg                 | 3.400 kg                   |