## connecting the future





## TDS 65A RAL 7016, singlepack

Article number: 120500

## **Product description:**

TRIAX TD Dishes The difference is clear

Manufactured and tested to the highest standards of precision and quality, TRIAX's easy-to-install dishes offer outstanding performance, durability and reliability.

TDS: Steel TDA: Aluminium

- Unrivaled build quality, whether Steel or Aluminium
  - Hot-dip galvanized steel OR long lasting Aluminium for extra corrosion protection
  - TRIAX's unique cable protection system
  - Every part, every accessory is weatherproofed
  - 2 years corrosion warranty
  - 5 years functionality warranty
- Outstanding performance
  - High gain for an exceptional signal
- Quick and easy installation
  - One-click mounting system
  - Self-locking screw & nuts
- Logistic friendly
  - Single or Bulk packaging, according to customer needs

TRIAX is your reliable partner, with comprehensive service and support.

Click here to see our guide on how to install TRIAX satellite dishes.

## Specifications

ORDER INFORMATION	
EAN Number	5702661205002
CHARACTERISTICS	
F/D ratio	0,62
G/T LNB 0.7	16.0 dB/K
X-polarisation	≤ -25 dB
Offset angle	26°
Elevation range	090 °
FREQUENCY	
Frequency range	10.712.75 GHz
GAIN	
Gain @ 11.7 GHz	36 dBi
MECHANICAL	
LNB holder	40
Mast bracket diameter	3060 mm
Reflector type	Offset
Beamwidth	3.1 °
Main material	Galvanized steel (hot-dip)
Arm Colour	Raw
Height (cm)	66 cm
Width (cm)	60 cm
Colour	RAL 7016 - Anthracite grey
Packing QTY	1
Packaging Height	0,734 m
Packaging Width	0,684 m
Packaging Depth	0,100 m
Packaging Volume	0,050 m3
Net Weight	3,220 kg
Tara Weight	1,050 kg
Total Weight	4,270 kg