

BS127N

Battery, 12 V, 7.2 Ah (for 2010-1 & 2010-2 fire panels only, use BS127N-A for all other applications)

Product overview

Sealed Lead Acid battery 12 V / 7.2 Ah with Fast-on 4.8 mm terminal type.

Note: for 2010-1 & 2010-2 fire panels only, use BS127N-A for all other applications.



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS127N

Battery, 12 V, 7.2 Ah (for 2010-1 & 2010-2 fire panels only, use BS127N-A for all other applications)

Technical specifications

General

Product type	Sealed lead acid battery
--------------	--------------------------

Electrical characteristics

Nominal voltage	12 V
Nominal capacity	7.2 Ah
Internal approx. resistance	21 mohm

Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	2.16 A
Max. discharge current	35 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Physical dimensions	151 x 94 x 65 mm
Net weight	2.678 kg
Shipping weight	2.678 kg
Material	ABS
Terminal type	Fast-on 4.8 mm

Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliance	RoHS 2, WEEE
Certification	VdS



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit ie.firesecurityproducts.com online or contact your sales representative.

Last updated on 26 February 2024 - 17:19