SW21AB-V2

BLUSTREAVA-

2 x Input HDMI 2.0 Switcher

Description

4K **AUTO** Our SW21AB-V2 is a 2-Way HDMI switch with integrated audio HDCP 2.2 breakout. The switch supports full HDMI 2.0 and HDCP 2.2 with video Hz 4:4 resolutions up to and including 4K @ 60Hz 4:4:4. **EDID** AUDIO HDR MANAGEMEN BREAKOUT 196mm **BLU**STREA// 2-Way 4K HDMI 2.0 Switch 32mm ₼ መ መ Output Select Input 1 Input 2 IR 3210 SW21-V2 0000 ((\bigcirc) _____ 32mm _____ SPDIF L/R IR Ext. EDID DC 5V Input 1 Input 2 Output Audio Out

Key Features

- Features 2 x HDMI inputs which can be switched to a single HDMI output
- Auto-switching (HPD sensing) capabilities can be enabled / disabled
- Supports full HDMI 2.0 specification 4K UHD video (4K @60Hz 4:4:4)
- HDCP 2.2 compliant
- Supports 3D signal display
- Supports CEC bypass (Consumer Electronics Control)
- Supports all industry standard video resolutions including VGA-WUXGA and 480i-4K

- Supports all known HDMI audio formats including Dolby TrueHD, Dolby Atmos, Dolby Digital Plus and DTS-HD Master Audio transmission
- HDMI audio breakout to analogue L/R audio and Coaxial digital outputs concurrently
- Control via front panel and IR (remote control included)
- Advanced EDID management





SW21AB-V2

BLUSTRE/////-->

Connectivity

- Video Input Connectors: 2 x HDMI Type A
- Video Output Connectors: 1 x HDMI Type A
- IR Input Ports: 1 x 3.5mm stereo Jack
- Audio Output Connectors: 1 x RCA (S/PDIF), 1 x Analogue audio L/R (3.5mm stereo Jack)

Included Accessories

IR Remote	1 x SW21 Remote
Rack Mount	Mounting brackets
Power Supply	5V/2A DC screw connector

Regulatory Compliance



Auto Switching	
IR	
Front Panel	



Specifications

• Shipping Weight: 0.8kg

• Dimensions (W x D x H): 196mm x 104mm x 32mm

• Operating Temperature: 32°F to 104°F (0°C to 40°C)

• Storage Temperature : -4°F to 140°F (-20°C to 60°C)



