

Cabinets

Wall Mounting Cabinets - RackyRax Pro Range

The compact design of the 19" Wall Mounting Cabinets make them ideal for smaller networks and work groups. The cabinets are available in various sizes and are supplied fully assembled. Each cabinet comprises a welded steel frame and adjustable front and rear 19" mounting profiles**. Cable access positions with removable plates are situated in the top and bottom of the cabinet. The cabinets feature a ventilation slots in the top, have a lockable glass front door, and removable, lockable side panels (barrel locks). The cabinet is finished in a high quality attractive black.



Features & Benefits

- Ventilated top
- Adjustable mounting posts
- Removable, lockable side panels (barrel locks)
- Cable entry with sliding cover in base and top
- Lockable glass front door
- Supplied fully assembled
- Can be supplied flat pack
- Barrel locks on the side panels

Technical Data	
Colour	RAL 9005 Black colour
Standards	ISO9001-2015 TS EN 61587-1 :2012, 5.2.1 and 5.2.2 CE According the IEC/ISO 17050 - EN 62208:2011 & EN 60335-1
Material	Sheet Steel, DIN EN 10130-99 / DC-01 6112 / DC-7122
IP Rating	IP20

** Please note - the 450mm deep (RR-W1) Cabinets do not have rear mounting posts. Use Cantilever shelves which are secured from the front. If Rear mounting posts are required, these can be supplied separately and attached on site.

Cabinets

Wall Mounting Cabinets - RackyRax Pro Range

Part Number 550 x 450	U Height	W (mm)	D (mm)	H (mm)	Max Internal Depth
RR-W1-6-G	6U	550	450	348	410
RR-W1-9-G	9U	550	450	481	410
RR-W1-12-G	12U	550	450	615	410
RR-W1-15-G	15U	550	450	748	410
RR-W1-18-G	18U	550	450	881	410
Part Number 550 x 550	U Height	W (mm)	D (mm)	H (mm)	Max Internal Depth
RR-W2-6-G	6U	550	550	348	510
RR-W2-9-G	9U	550	550	481	510
RR-W2-12-G	12U	550	550	615	510
RR-W2-15-G	15U	550	550	748	510
RR-W2-18-G	18U	550	550	881	510
RR-W2-21-G	21U	50	550	1015	510
Part Number 600 x 600	U Height	W (mm)	D (mm)	H (mm)	Max Internal Depth
RR-W5-6-G	6U	600	600	348	560
RR-W5-9-G	9U	600	600	481	560
RR-W5-12-G	12U	600	600	615	560
RR-W5-15-G	15U	600	600	748	560
RR-W5-18-G	18U	600	600	881	560
RR-W5-21-G	21U	600	600	1015	560